



DET NORSKE VERITAS

EC-Type Examination Certificate

[2] EQUIPMENT OR PROTECTIVE SYSTEM INTENDED FOR USE IN POTENTIALLY EXPLOSIVE ATMOSPHERES DIRECTIVE 94/9/EC

[3] EC-Type Examination Certificate Number: DNV 12 ATEX 14348X

[4] Equipment or Protective System: Ex d motors

[5] Applicant - Manufacturer or Authorized representative: HIGEN MOTOR CO., LTD.

[6] Address: 74-5, SEONGSAN-DONG, CHANGWON-SI

KOREA

[7] This equipment or protective system and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

[8] DNV, notified body number 0575 in accordance with Article 9 of Council Directive 94/9/EC of 23 March 1994, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential reports listed in section 14.

- [9] Compliance with the Essential Health and Safety Requirements has been assured by compliance with: EN 60079-0: 2009 and EN 60079-1: 2007
- [10] If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.
- [11] This EC-TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified equipment or protected system. If applicable, further requirements of this Directive apply to the manufacturer and supply of this equipment or protective system.
- [12] The marking of the equipment or protective system shall include the following:

€x>

II 2 G

Ex d IIB T5/T6 Gb -20° C \leq Ta \leq +50°C

Høvik, 2013-01-18 for Det Norske Veritas AS

/ Geir Hørthe

Certification Manager



Notice: This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.

The digitally signed and electronically distributed document is the original and valid certificate. Ref.: www.dnv.com/digitalsignatures
berson suffers loss or damage which is proved to have been caused by any negligent act or amission of Det Norske Veritas; then Det Norske Veritas shall pay compensation to such person for his proved direct loss or damage er, the compensation shall not exceed an amount equal to ten times the fee charged for the service in question, provided that the maximum compensation shall never exceed USD 300.000. In this provision "Det Norske Veritas as well as all its subsidiaries, directors, officers, employees, agents and any other acting on behalf of Det Norske Veritas."









[13]

Schedule

[14] EC-TYPE EXAMINATION CERTIFICATE No.: DNV 12 ATEX 14348X

Certificate History

Revision	Description	Report no.	Issue date	
-	Original certificate	2012-9619	2013-01-18	

[15] Description of Equipment or Protective System

Three-phase one speed ac squirrel cage induction motor intended to be used with a variable speed drive. The temperature limitation is based on the torque limiting capacity of the drive and temperature sensing elements in the windings. Cooling is an external blower. The windings are of class F insulation.

Duty Types: TEFC(S1 and S3~S9), TENV(S2 30min.), TEAO(S1)

TEFC: External fan is attached to the shaft end for the circulation of air around the enclosure.

TENV: Cooling without using a fan. (Duty Type:S2 30min.)

TEAO: Cooling air is blown over the totally enclosed motor surface by a separately fan.

Motors without fan can deliver same output power provided installation is according to IC418.

(Direct driven fan motors without cooling fan on the motor.)

The 2 pole to 8 poles protection types and motors rating

Type Identification	Ex code	IP	Operation mode and T classification	Electrical Data	Rpm
DB3D 280M	Ex d IIB	56	(S1 – S9)T5 or (S1 - S2)T6	200-690V 50/60Hz 44 – 160kW	750 - 3600

Nomenclature

D	С	3	D	280	M	04	B30	FC	380	1	60
1	2	3	4	(5)	6	7	8	9	(10)		10

1st; D: Flameproof

2nd; B:IIB

3rd; three phase 1 speed

4th; terminal box protection type, D:Ex d

5th; frame number

6th; core length

7th; number of poles, 02: 2poles, 04: 4poles, 06: 6poles, 08:8poles

8th; mounting, B3, B5, B35, V1, V3, V5, V6

9th; ventilation, FC:TEFC, NV:TENV, AO:TEAO

10th; voltage & frequency

[16] Project No.: PRJC-224371-2010-PRC-KOR

If any person suffers loss or damage which is proved to have been caused by any negligent act or omission of Det Norske Veritas, then Det Norske Veritas shall pay compensation to such person for his proved direct loss or damage. However, the compensation shall not exceed an amount equal to ten times the fee charged for the service in question, provided that the maximum compensation shall never exceed USD 300.000. In this provision "Det Norske Veritas shall mean the Foundation Det Norske Veritas as well as all its subsidiaries, directors, officers, employees, agents and any other acting on behalf of Det Norske Veritas.







EC-TYPE EXAMINATION CERTIFICATE No.: DNV 12 ATEX 14348X

Descriptive Documents

Number	Title	Rev.	Date
4682EHCT01	Motor Assembly 280M IIB(2 Pole)	3	2013.01.07
4682EHCT02	Motor Assembly 280M IIB(4,6,8 Pole)	3	2013.01.07
2242ET0001	Parts list 280M IIB(2 Pole)	0	2012.02.29
2242ET0002	Parts list 280M IIB(4,6,8 Pole)	0	2012.02.29
3844EZ0025	Labeling 280M IIB	0	2012.02.29
3210E2T001	Frame 280M Horizontal	0	2012.02.29
4810E2T001	Bracket 280Fr. Front&Rear(48Pole)	1	2012.12.12
4810E2T002	Bracket 280Fr. Front&Rear(2Pole)	1	2012.12.12
3550E2T001	Bearing Cover-IN.Front&Rear(48Pole)	0	2012.02.29
3550E2T002	Bearing Cover-OUT.Front&Rear(48Pole)	0	2012.02.29
3550E2S003	Bearing Cover-INFront&Rear(2Pole)	3	2012.12.13
3550E2S004	Bearing Cover-OUT.Front&Rear(2Pole)	2	2012.12.13
4830E3T001	Bushing Cable	1	2012.01.23
4830E3N001	Bushing Cable	0	2010.12.01
4370E3T001	Shaft 4,6,8Pole	0	2012.02.29
4370E3T002	Shaft 2Pole	0	2012.02.29
3040E3T001	Terminal Base	1	2012.11.19
3550E3T001	Terminal Cover	1	2012.11.19
5900KK4003	Fan 2Pole	0	2012.02.29
5900KK2007	Fan 4Pole	0	2012.02.29
2M96018	Fan 6,8Pole	0	2008.03.14
3550K3T026	Fan Cover 28Pole	0	2007.09.07
3211EHCT01	Frame Assy	0	2012.02.29

[17] Special Conditions for Safe Use

Repairs of the flameproof joints must be made in compliance with the structural specifications provided by the manufacturer. Repairs must not be made on the basis of values specified in tables 1 and 2 of EN/IEC 60079-1.

The tensile strength of the fastener elements of each part of the flame proof casing must be at least equal to 1220N/mm².

[18] Essential Health and Safety Requirements

See part 9 of this certificate

END OF CERTIFICATE

If any person suffers foss or damage which is proved to have been caused by any negligent act or omission of Det Norske Veritas, then Det Norske Veritas shall pay compensation to such person for his proved direct loss or damage. However, the compensation shall not exceed an amount equal to ten times the fee charged for the service in question, provided that the maximum compensation shall never exceed USD 300.000. In this provision "Det Norske Veritas" shall mean the Foundation Det Norske Veritas as well as all its subsidiaries, directors, officers, employees, agents and any other acting on behalf of Det Norske Veritas.

